

PU FEST TURBO

Two-component polyurethane sealer for resin, cement and microcement floors for indoor and outdoor use.

PRODUCT DESCRIPTION



A two-component polyurethane sealer with very high surface hardness and excellent flexibility. It does not turn yellow, it is resistant to UV rays providing very high durability.

PU FEST TURBO can be used in many ways:

- as concrete and stone sealer for indoor and outdoor use;
- to protect heavy traffic industrial floors exposed to high mechanical loads;
- to protect the surface of epoxy resin coatings, polyurethane resin, cement coatings on floors and walls;
- for the protection of microcement and cement coatings with high and low porosity.

The product is for professional use only.

HOW TO USE



The surface must be perfectly hardened, load-bearing, dry, clean and free of dust, waxes and oils. The container with PU FEST TURBO sealer should be well shaken. Add hardener as indicated on the package. The hardener in a ratio of 2: 1 (2 parts by weight of component A: 1 part by weight of component B) is poured into the container with the sealer and mixed thoroughly. Leave the container open for about 10 minutes, then mix again. Apply with a high-quality roller with a bristle length of min. 6 mm. The second layer of PU FEST TURBO can be applied after 4 hours without the need to sand or after 24 hours after sanding the surface with 220 grit sandpaper.



Do not use PU FEST TURBO during the hottest hours of the day, when weather conditions are not favorable, as well as on damp grounds.

SAFETY AND HEALTH



Component A

- Highly flammable liquid and vapor.
- Causes serious eye irritation.
- May cause drowsiness or dizziness.
- Frequent contact may cause dryness and cracking of the skin.
- If you need medical attention, have a container or product label on hand.
- Keep out of the reach of children.
- Keep away from heat / sparks / open flames / hot surfaces. No smoking.
- Keep container tightly closed.
- Use only outdoors or in a well-ventilated room.
- Wear protective gloves / protective clothing / eye protection / face protection.
- Call a POISON CENTER or doctor / physician if you feel unwell.
- Dispose your waste in dedicated collection points.



Component B

- Highly flammable liquid and vapour.
- Harmful if inhaled.
- May cause an allergic skin reaction.
- Contains isocyanates. May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Keep away from heat / sparks / open flames / hot surfaces. No smoking.
- Keep container tightly closed.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves / protective clothing / eye protection / face protection.
- Call a POISON CENTER or doctor / physician if you feel unwell.
- Dispose your waste in dedicated collection points.



PACKAGING

PU FEST TURBO is available in packages:

- 5 kg component A + 2,5 kg component B

SPECIFICATIONS

- Mixture ratio: 2 parts by weight of component A: 1 part by weight of component B
- Color: transparent
- Application temperature: + 10 ° C ÷ + 25 ° C
- Dry on touch after 2 hours.
- Light pedestrian traffic is possible after 24 hours, full load after 7 days.
- Consumption: 0,1-0,15 kg / m²
- Gloss level: satin mat
- Pot life: 45 minutes
- Shelf life: 6 months.

